

## 1. Product Introduction

MediaJack-Mini is Bittel's latest innovation for hotels customized need for compact outlook and powerful functions Mediajack solution. With most popular interfaces and compact outlook of 86mm \* 86mm panel mountable on a standard 86mm back box, MediaJack-Mini is emerging as ideal solution for top end hotel and resorts. With wired/wireless music inputs, HDMI video inputs, dual USB chargers compatible with iPads, MediaJack-Mini is a one stop solution for guests demands for power charging, music/audio playing and movie/video watching, thus emerges as the ideal solution for both business and leisure guests.

## 2. Product Photo



**Model: MediaJack-Mini**

Material: Acrylic surface+Brushed Aluminum Alloy Frame

Color: Silver, Black, Champagne

## 3. Interfaces Illustration

- HDMI Port (HDMI 1.4)
- Stereo Bluetooth
- Mini Audio Port
- Dual USB chargers of 0.5A and 2.1 A, compatible for iPad charging.

## 4. Unique Features

- Compact outlook with only 86mm X 86mm Panel, mountable on standard BS/EU standard/86 standard back box. No need for extra back box deploying.
- Unique Acrylic panel plus brushed aluminum alloy frame with multiple colors optional for flexible customization.
- HDMI port of 1.4 protocol compatible with latest HD 1080P audio/video content.
- HDMI CEC function of HDMI input makes plug & play a snap.
- Stereo Bluetooth with A2DL features enables high definition wireless music streaming to TV.

- Direct pairing of Bluetooth without PINs gives easy usage to guests.
- Mini Audio Port for cabled audio input for more classic input connection.
- Dual USB chargers of 0.5A and 2.1 A, ready to charge all kinds of smartphones/tablets, including power-hunger iPad. Samsung/Blackberry/Apple iDevices compatible.

## 5. Dimensions and Installation

- External size: 86mm\*86mm
- Internal size:64mm\*58mm\*45mm (L\*W\*D)
- DC Adapter mounting type: External.
- Mounting type: Wall mounting/desk mounting
- In-wall cables: HDMI cables, mini audio cables.

**Caution: Cabling to the TV shall be done from TV side to Mediajack-Mini mounting position. PH type HDMI plugs shall be protected from rough handling.**

## 6. Technical Specification

### 6.1 Supporting Format

- HDMI Output Format: 1080P/ ( 60Hz)/720P ( 60Hz)
- HDMI Input Format:
  - 480i/480P
  - 576i/576P
  - 720P (50HZ/60HZ)

### 6.2 Parameters

Power	Input AC 100V-240V/50Hz Output DC12V 1.5A
Watt	6W
Audio/Video Input	HDMI ( 1.4 ), Mini Audio, Stereo Bluetooth
Video Ouput	HDMI ( 1.4 ) 1080P/60Hz, Mini Audio
Communication Protocol	CEC
USB	DC5V 2.1A/DC5V 0.5A
AC Power	Same as local power
Working Environment	<p>Working Temperature: +5°C ~ +35°C;          Working Humility: 25% ~ 90%          Storage Temperature: -15°C ~ +45°C;          Storage Humility: ≤80%          Atmospheric Pressure: 86 ~ 106KPa</p> <p>Note:          In order to avoid causing damages, media panel should be put in working temperature for over 3 hours before installation and use if storage temperature is lower than 5°C.</p>